

CTL / CTL Plus+

- Contactless temperature data logger
- Utilizes mobile app
- Pre-programmed to customer specifications
- High accuracy, Fast response time
- Large memory capacity
- Long battery life
- 7 LED indicators
- Waterproof pouch
- RAO (Radio Always On) CTL plus+ only



CERTIFICATIONS



21 CFR Part 11





Product Specifications (continued on back)

Logger	Specifications		
Transmission Range	Approximately 30.5m (100ft) line-of-sight		
Logging Rate	20 seconds to 18 hours		
Logging Modes	Temperature/Event ID/Date& Time		
Start Modes	Push button or via mobile app		
Stop Modes	When memory full, push button or via mobile app		
Time Accuracy	±5 minute per month at 25°C (77°F)		
Battery Life	1 year / 1 trip (turned on)		
Memory	4000 Records + 62 Events (16KB) or 8000 Records + 128 Events (32KB)		
LED	5 LEDs for alarm: HH, H (red), OK (green), L, LL (blue); 1 LED for status (orange); 1 LED for RF module (white)		
Push Button	1 with 4 different activities: check status & manual log (less than a second)/RF on & off (3-4 seconds)/Start (7-9 seconds)/Stop (10-12 seconds)		
Size	95mm x 50mm x 9mm		
Weight	20g		
Environmental Rating	IP67, Completely food safe		
Packaging	Plastic sleeve		

Temperature Sensor	Specifications
Temperature Range	-30 °C to +70 °C
Temperature Accuracy	±0.2°C

Mobile App	Specifications		
os	Android 4.0 or higher, iOS		
Application features	Communicate with device, sync date/time, setup the device and log parameters, do wnload the records, calculate and analyze the data and calculate statistic parameter s (max, min, avg, MKT, log duration, individual thermal zone durations Show data in table and chart, generate report		
Report format	PDF, Excel, Raw Data		
Export mode	Sending by email, share by messenger app (WhatsApp, Skype, Telegram)		
Application Update	Automatically via Google Play or Apple App Store [CTL Cryopak Contactless Logger App]		

Available Versions					
Product Code	Number of logs	Audio Buzzer	RF Always On (RAO)		
CTL - ST - 4	4K	N/A	N/A		
CTL - ST - 4 - B	4K		N/A		
CTL - ST - 4 - B - RAO	4K				
CTL – ST – 8	8K	N/A	N/A		
CTL - ST - 8 - B	8K		N/A		
CTL - ST - 8 - B - RAO	8K				



Canada

Europe